



ELF EVOLUTION FULL-TECH RPX 5W-30 is a very high performance lubricant using ELF Advanced Synthetic Technology, specially formulated to ensure a very large coverage of manufacturers requirements such as Renault, PSA and Mercedes.

Technical Data Sheet

International Specifications

ACEA C2, C3
API SP

Manufacturers Approvals

Approved :
MB-APPROVAL 229.52
PSA B71 2290
RENAULT RN17

Meets the requirement of :
MB-229.51, MB-229.31, MB-226.52
RENAULT RN0710, RENAULT RN0700

Suitable for :
FIAT 9.55535-S1
18-1811
TOYOTA

* Refer to the maintenance book of your vehicle to know the recommendation of the manufacturer.

1 - Applications

ELF EVOLUTION FULL-TECH RPX 5W-30 is a very high performance lubricant using ELF Advanced Synthetic Technology, specially formulated to ensure a very large coverage of manufacturers requirements such as Renault, PSA and Mercedes.

ELF EVOLUTION FULL-TECH RPX 5W-30 is compatible with latest post-treatment systems: DPF, GPF, SCR, NOx-Trap. It guarantees its efficiency to allow better and sustainable air quality respect.

2 - Customer Benefits

Ensures your engine longevity and best performance thanks to excellent wear protection and deposit prevention.

Best in class oxidation prevention and low engine oil volatility to ensure low oil consumption.

Guarantees post treatment system efficiency to allow better and sustainable air quality respect.

3 - Characteristics

TEST	TEST METHOD	UNITS	VALUE
Density at 15°C	ASTM D1298	kg/m ³	851.7
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s	72.81
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	12.15
Viscosity index	ASTM D2270	-	165
Pour point	ASTM D97	°C	-39
Flash point	ASTM D92	°C	237
TBN	ASTM D2896	mgKOH/g	8,6
Sulphated Ash	ASTM D874	% m/m	0.7

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

4 - Recommendations for Use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements.

Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

5 - Health, Safety and The Environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

The SDS is available on request from your local reseller and at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.